



Patents received or pending.

Note: Dimensional Tolerances: ±1/4"

	JL535	JL635
Drop-in-Hole Size:	58" x 40"	70" x 40"
Operating Capacity:	43 gal	49 gal
Overflow Capacity:	70 gal	80 gal
Floor Loading / sq.ft.:	44.4 lbs	40.9 lbs
Cartoned Wt:	114 lbs	129 lbs
Cartoned Wt: Soaker	86 lbs	88 lbs
Cube:	36.2 cu. ft.	43.2 cu. ft.

Construction: Fiberglass reinforced acrylic bath with Level Form™ full-support base

We provide products listed with Underwriters Laboratories, Inc. (UL), International Association of Plumbing and Mechanical Officials (IAPMO), and Canadian Underwriters Laboratory (CUL). Consult factory with your listing requirements.

Standard		<p>1 hp, variable speed blower with integral air heater and electronic control with 20 minute timer and automatic purge cycle. Controller operates blower, blower speed for continuous or massage mode. Requires one (1) 120V 20A dedicated GFCI-protected circuit.</p>
Signature		<p>1 hp, variable speed blower with integral air heater and digital control with 20-minute timer and automatic purge cycle. Controller operates blower, blower speed for for continuous, wave or pulse massage mode. Shows blower speed and time remaining. Includes LED mood light and floating universal remote control that operates all bath functions plus TV, DVD, CD, etc. Requires one (1) 120V 20A dedicated GFCI-protected circuits.</p>