



Patents received or pending.

Note: Dimensional Tolerances: ±1/4"

	VL5535	VL635
Drop-in-Hole Size:	See Diagram	See Diagram
Operating Capacity:	43 gal	46 gal
Overflow Capacity:	70 gal	74 gal
Floor Loading / sq.ft.:	44.4 lbs	42.3 lbs
Cartoned Wt: AirMasseur™	113 lbs	113 lbs
Cartoned Wt: Soaker	72 lbs	80 lbs
Cube:	39.7 cu. ft.	43.2 cu. ft.

Construction: Fiberglass reinforced acrylic bath with Level Form™ full-support base

We provide products listed with Underwriters Laboratories, Inc. (UL), International Association of Plumbing and Mechanical Officials (IAPMO), and Canadian Underwriters Laboratory (CUL). Consult factory with your listing requirements.

Standard	 <p>1 hp, variable speed blower with integral air heater and electronic control with 20 minute timer and automatic purge cycle. Controller operates blower, blower speed for continuous or massage mode. Requires one (1) 120V 20A dedicated GFCI-protected circuit.</p>
Signature	 <p>1 hp, variable speed blower with integral air heater and digital control with 20-minute timer and automatic purge cycle. Controller operates blower, blower speed for for continuous, wave or pulse massage mode. Shows blower speed and time remaining. Includes LED mood light and floating universal remote control that operates all bath functions plus TV, DVD, CD, etc. Requires one (1) 120V 20A dedicated GFCI-protected circuits.</p>