




SPECIFICATIONS

LC635

Whirlpool Bath



Drop In Hole Size



Note: Dimensional Tolerances $\pm 1/4$

Drop-in-Hole Size:

Operating Capacity:

Overflow Capacity:

Floor Loading / sq.ft.:

Cartoned Wt:

Cube:

LC635

See Diagram

66 gal

86 gal

56.2 lbs

158 lbs

51.8 cu. ft.

Construction: Fiberglass reinforced acrylic bath with Level Form™ full-support base

We provide products listed with Underwriters Laboratories, Inc. (UL), International Association of Plumbing and Mechanical Officials (IAPMO), and Canadian Underwriters Laboratory (CUL). Consult factory with your listing requirements.

Standard



1 1/2 hp, 1 speed pump, touch control with low water level sensor, and a 20-minute timer. Light indicates when pump is on. Requires one (1) 120V 20A dedicated GFCI-protected circuits.

Signature



1 1/2 hp, 3 speed pump, digital control with low water level sensor, water temperature sensor, 20-minute timer, automatic 1.5 kW heater, and a front access LED moodlight. Shows water temperature and time remaining. Floating Universal Remote Control operates all bath and light functions plus TV, VCR, CD, etc. Requires two (2) 120V 20A dedicated GFCI-protected circuits.